

FIRE SAFE TEST CERTIFICATE

CERTIFICATE NUMBER: FS-1106-722271470

CLIENT

OMAL S.p.a.

Via Ponte Nuovo, 11 25050 Rodengo Saiano (BS)- Italy

TEST LOCATION:

OMAL S.p.a.

Via Brognolo, 12 25050 Passirano (BS), Italy

REPORT NUMBER:

SCOPE OF REPORT:

Fire Safe test carried out according to: ISO 10497 Third Edition February 2010 &

API 607 Seventh Edition 2016.

QUALIFIED VALVE

Size:

2"

Rating Class:

4000 PSI

Drawing N°:

Y_6488

Type/Model:

TWO PIECES SCREWED FLOATING BALL VALVE / **KRATOS**

Valve Material:

ASTM A350 LF2

Seat Insert Material:

DEVLON

Gasket Material:

GRAPHITE, TFM1600 & DEVLON (V CHEVRON)

For further details of test arrangements and test results, please see Fire Test Report No.66 here with attached and duly endorsed.

RANGE AND TYPE OF VALVES COVERED (ISO 10497:2010 & API 607 7th Ed. 2016):

NPS 2" and below 2".1/2; 3"; 4" (DN 50 and below 65; 80; 100)

PSI 8000 and below (552 Bar and below)

TÜV **INSPECTOR** S.Mastrogiacomo



CERTIFICATION DATE

29/06/2022

