



**BUILT TO MOVE:
COMPACT, LIGHT, AND SAFE.**
OMAL IS WITH YOU.

WWW.OMAL.COM

Specialists in
valves and **actuators**
since 1981.





MOBILITY: GAS TRANSPORTATION & LPG



MAGNUM WAFER

TPED (EN 14432)



KRATOS

TPED (ISO 23826)



**AGO
PNEUMATIC ACTUATORS**



APPLICATIONS



TANK WAGON



TECHNICAL DETAILS

MAGNUM

TPED (EN 14432)

WAFER BALL VALVES



SPECIFICATIONS

- **Size:**
 - DN 15 ÷ DN 100 [mm]
 - 1/2" ÷ 4" [inch]
- 🔧 **Body material:**
 - A105 Carbon steel
 - 316 Stainless steel
- 🔧 **Available seats:**
 - PTFE Modified
- 🔧 **End connections:**
 - Flanged RF
- 🔧 **Pressure class:**
 - ANSI 150-300; PN 16-40
- ⚙️ **Options:**
 - Mono-directional ball
 - Locking device
 - Stem Extension
 - Bottom tank
 - Oxygen use (on request*)
 - Hydrogen use (on request*)
- 🏆 **Certifications:**
 - Ex CE/UKCA
 - Pressure Equipment CE/UKCA
 - SIL (up to SIL3)
 - TA Luft & Fugitive Emission
 - Fire Safe

KRATOS

TPED (ISO 23826)

HIGH PRESSURE BALL VALVES



SPECIFICATIONS

- **Size:**
 - DN 8 ÷ DN 50 [mm]
 - 1/4" ÷ 2" [inch]
- 🔧 **Body material:**
 - A350-LF2 Carbon steel
 - 316 Stainless steel
- 🔧 **Available seats:**
 - PEEK
- 🔧 **End connections:**
 - ISO 228-1
 - NPT (ANSI B1.20.1)
- 🔧 **Max pressure:**
 - PN 400 (varies by size)
- ⚙️ **Options:**
 - Oxygen use (on request*)
 - Hydrogen use (on request*)
 - Mono-directional ball
 - BW / SW connection
 - Stem Extension
- 🏆 **Certifications:**
 - Ex CE/UKCA
 - Pressure Equipment CE/UKCA
 - Fugitive Emission
 - SIL (up to SIL3)
 - Fire Safe

AGC

ALUMINIUM PNEUMATIC ACTUATORS



SPECIFICATIONS

- ✓ **Type:**
 - Scotch yoke
- 🔄 **Nominal torque:**
 - DA (Double acting):
8 Nm ÷ 8000 Nm
70 in-lbs ÷ 70806 in-lbs
 - SR (Spring return):
15 Nm ÷ 4000 Nm
133 in-lbs ÷ 35403 in-lbs
- **Size:**
 - DA 8 ÷ DA 8000
 - SR 15 ÷ SR 4000
- 🔧 **Body material:**
 - Aluminium
- 🔧 **Variations:**
 - Double acting
 - Spring return N.C. - N.O.
- ⚙️ **Options:**
 - Low temp. version:
-50°C / -58°F
 - High temp. version:
+150°C / +302°F
 - Adjustable rotation
 - Surface treatments
- 🏆 **Certifications:**
 - Ex CE/UKCA
 - SIL (up to SIL3)





Our history



Other applications



Sustainability



OMAL S.p.A. Società Benefit

Headquarter Via Ponte Nuovo, 11 - 25050 Rodengo Saiano (BS), Italy

Production Site Via Brognolo, 12 - 25050 Passirano (BS), Italy

Ph. +39 030 8900145 • Fax +39 030 8900423 • info@omal.it

OMAL USA Corp.

1835 Airport Exchange Blvd, Suite 100- 41018 Erlanger (Kentucky), USA

Ph. +1 (859) 900-2108 • info@omal.com

OMAL Asia Pacific Ltd.

26/73, Moo 7, Racha Thewa Sub-district, Bang Phli District,
Samut Prakan Province, (Bangkok), Thailand

Ph. 02-117-1188 • info@omal.co.th

www.omal.com