

## **FUGITIVE EMISSION CERTIFICATE**

**CERTIFICATE NUMBER:** 

FG-063579-645

CLIENT:

**OMAL** 

ADDRESS:

Via Ponte Nuovo, 11 25050 Rodengo Saiano (BS) - Italy

REPORT NUMBER:

36

SCOPE OF REPORT:

Fugitive Emission test carried out according to: ISO 15848-1 Edition 2015

max BAR:

50,0 Bar

max °C:

+200°C

QUALIFIED VALVE:

Size:

1" (Stem Dia. 13mm)

Rating Class:

ANSI 300

Drawing N°:

Y 4697

Type:

SPLIT BODY BALL VALVE

RANGE AND TYPE OF VALVES COVERED:

ISO FE BH-C03-SSA 0-t(-29°C, 200°C)-ANSI300-ISO 15848-1

In accordance with ISO 15848, we also extend the certification to valve

with same stem and body seals material, design (shape) and

construction, with stem size 50% lower and 200% higher than stem

ested.

Paragraph 8 e): Stem tested Ø13 mm => Ø 6.5 mm ≤ Stem certified ≤ Ø26

mm

Paragraph 8 f): Pressure ≤ANSI300

The valve certified in accordance with paragraph 8 e) & 8 f) are:

From DN15 FB to DN 80 FB, ANSI cl. ≤300 and PN ≤ 40 of series M1, M4,

T1

From DN20 RB to DN 100 RB, ANSI cl. ≤300 and PN ≤ 40 of series T1. From DN15 FB to DN 50 FB, ANSI cl. ≤300 and PN ≤ 40 of series M5, M6,

T2, T3.



CERTIFICATION DATE 07/09/2015

